

Podium Substrate

All top, side panels, and cross bracing are high strength alloy 6063-T6 extruded aluminum with a smooth finish. Podium is constructed of individual aluminum boards with laminate adhered to surface. Top surfaces are .065" thick with integral stiffener ribs. All edges have a flat edge, including corners. Painted surfaces are thermal set powder-coated finishes and have the hardest surface and maximum scratch/mark resistant qualities in the industry. Fasteners are aluminum and/or zinc-plated steel.

Sustainability

Aluminum extrusions contain 70% **recycled** aluminum; 10% is post-consumer content, and 60% pre-consumer content. Southern Aluminum products are 100% recyclable. Laminate is **GREENGUARD** certified for low emissions. Laminate adhesive does not contain urea-formaldehyde resins.

Podium Top

Podium top measures 18" x 20" with covered grommet mounted from left-hand side. Top perimeter is 2mm x 1" PVC vinyl edge band with 1/2" paper lip. Inlay surface on podium top and front panel is high pressure laminate with premium scratch resistant finish, permanently bonded with contact adhesive. Manufacturer provides 5-year laminate warranty.

Podium Pedestal

Podium features 10 1/4" wide x 6" shelf and paper tray which are finished in thermal set powder-coat paint. Panel is attached to top and base with zinc-plated fasteners. Total podium height is 46 1/2" high.

Podium Base

Base surface is ribbed vinyl mat and measures 16" x 24" with grommet hole to allow for wire exiting. Rubber podium feet are 3/4" OD x 1" high. Caster wheels are 3/4" x 1 5/8" for easy maneuvering.

Available Sizes

Size	Model #
24 1/4" x 16 1/4" x 43"	POD

